

Villa Lin

Paint with linseed oil for exterior wood

- ✓ Penetrates deep into wood's surface
- ✓ Dries faster than traditional linseed oil paints
- ✓ Suitable for wooden buildings in areas of historical value
- ✓ Very easy to paint
- ✓ Wide range of shades (compared to traditional lin seed oil paints)



TECHNICAL DATA	
Product information	Paint with linseed oil for wooden facades. Suitable for wooden buildings in areas of historical value.
Fields of application	Sawn and planed wooden surfaces outdoors (weatherboards, doors, window frames, fences etc). Also suitable for thermo treated wood.
Gloss	Semi-gloss
Coverage per coat	4-8m ² /l - for sawn wood, 9-12m ² /l - for planed wood.
Tinting	The paint can be used white (A base) or tinted according to Tikkurila Puutalot color card (A and C bases). Tinted products cannot be exchanged.
Application method	Brush
Drying time at +23 °C, RH 50%	4 hours – touch-dry, 24 hours – recoatable. Air humidity and temperature can strongly affect drying times
Thinner	<i>Special Solvent</i> thinner
Cleaning of painting tools	Clean painting tools from liquid paint residues immediately after finishing the work, then wash with <i>Special Solvent</i> .
Storage time	In tightly closed original container until best before date. Production/ best before dates are stated on a can. Reseal once opened cans well for next use.
Solid content	About 62% v/v
Density	1,3 kg/l, ISO 2811
Weather resistance	Good, also in industrial and marine atmosphere.
Packaging	0,9 L; 2,7 L; 9 L;



INSTRUCTIONS FOR USE

PREPARATION

Unpainted surfaces:

Clean the surface of any dirt or loose material. Wash greasy and dirty surfaces with cleansing agent *Special Clean* according to instructions, rinse with water and allow to dry. Wash down surfaces affected by mould with *Tikkurila Homeenpoisto* according to instructions, rinse with water and allow to dry. Prime new wooden surfaces already in construction phase as early as possible with *Villa Protekt*. Treat the end grains of the wood with particular care. Remove loose resin from knots. Prime metal surfaces (e.g. nail heads) with suitable primer for metal.

Previously painted surfaces:

Clean the surface from residues of old paint with scraper or steel brush. Wash greasy and dirty surfaces with cleansing agent *Special Clean* according to instructions, rinse with water and allow to dry. Wash down surfaces affected by mold with *Tikkurila Homeenpoisto* according to instructions, rinse with water and allow to dry. Prime bare wooden surfaces with *Villa Protekt*. Treat the end grains of the wood with particular care. Remove loose resin from knots. Prime metal surfaces (e.g. nail heads) with suitable primer for metal.

PAINTING CONDITIONS

Surface should be clean and dry (relative humidity of wood less than 20%), temperature of ambient air should be at least +5°C, the relative air humidity below 80% during treatment and drying. Avoid excessive temperatures during painting.

PAINTING

Thoroughly mix paint *Villa Lin* before painting, thin the first layer of paint with *Special Solvent* if required up to 5% of volume. To obtain uniform and monochromatic coating, mix sufficient amount of tinted paint in one vessel prior painting. Apply with brush, 1-2 layers for new wooden surface, 1 layer for previously painted surface. Treat edges and ends of the wooden object with special care. NB! Prior to painting protect from spatter or temporarily cover plants and surfaces, which are not going to be painted.

CARE AND HANDLING OF SURFACE

Surfaces can be cleaned in 1 month after painting. Water spray is the most suitable method for cleaning. It should be taken into account that wet cleaning of the surface may change its colour, therefore cleaning area should be determined. Remove loose particles and dirt prior washing. To remove mould or algae apply *Tikkurila Homeenpoisto* and rinse well. Always overcoat the surface after mould removal. Surfaces painted with linseed oil containing paints when dried or stored in the dark have tendency to yellow. When yellowed surface is exposed to light, original shade will be restored.

ENVIRONMENTAL, SAFETY AND WASTE REGULATORY



Warning

UN 1263

Avoid release to the environment. Do not discharge the product into sewerage systems, watercourse, nor pour it onto the ground. Destroy liquid waste according to the local regulations for hazardous waste.

Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soaked in water and placed in a closed metal container before disposal.



Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% arom; 4,5-dichloro-2-octyl-

The data above is verified and correct, based on the laboratory tests as well as on practical experience. Our management system is certified according to the international standards ISO 9001 and ISO 14001. As a producer, we cannot be held responsible for any losses incurred upon non-compliance with the technical data sheets or application terms for a particular product.

AS TIKKURILA Liimi 5, 10621 Tallinn, Estonia, tel +372 650 11 11, fax +372 650 11 22, e-mail: info.ee@tikkurila.com

2H-isothiazol-3-one, 2-Octyl-2H-isothiazol-3-one and ethyl methyl ketoxime. WARNING. Flammable liquid and vapour. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Avoid breathing vapours. Wear protective gloves. In case of inadequate ventilation wear respiratory protection. Keep away from sparks and open flames. — No smoking. Dry and empty containers should be discarded in compliance with the local regulations. EU VOC limit value (subgroup A/d) - 300 g/l. Maximum content of VOC in product 300 g/l.

TRANSPORTATION

Unaffected by cold storage or transport.

ADDITIONAL PRODUCT INFORMATION

www.vivacolor.lv



The data above is verified and correct, based on the laboratory tests as well as on practical experience. Our management system is certified according to the international standards ISO 9001 and ISO 14001. As a producer, we cannot be held responsible for any losses incurred upon non-compliance with the technical data sheets or application terms for a particular product.

AS TIKKURILA Liimi 5, 10621 Tallinn, Estonia, tel +372 650 11 11, fax +372 650 11 22, e-mail: info.ee@tikkurila.com